



# Chongqing Cummins Engine Co. Ltd.

## Engine Data Sheet

CCEC

MODEL: NTA855-G1B

DATA SHEET: DS-819E

ONFIGURATION NO.: D093517DX02

PERFORMANCE CURVE: C-819E

CPL NUMBER: 1183

PRIME POWER 380 HP (284 kW) at 1500 r/min

DATE: 2007-1-25

STANDBY POWER: 430 HP (321 kW) at 1500 r/min

REVISION: 00

### GENERAL ENGINE DATA

Type.....	4-Cycle;In-line;6-Cylinder	
Aspiration .....	Turbocharged,Aftercooled	
Bore x Stroke - in.×in. (mm×mm).....	5.5 ×6	( 140 × 152 )
Displacement - in. <sup>3</sup> (L).....	855	( 14 )
Compression Ratio .....	14.0:1	
Firing Order .....	1-5-3-6-2-4	
Dry Weight		
--Fan to Flywheel Engine - lb. (kg).....	2870	( 1300 )
--Heat Exchanger Cooled Engine - lb. (kg).....	3095	( 1410 )
Wet Weight		
--Fan to Flywheel Engine - lb. (kg).....	2970	( 1350 )
--Heat Exchanger Cooled Engine - lb. (kg).....	3320	( 1510 )
Moment of Inertia of Rotating Components - With FW1109 flywheel - lb.ft. <sup>2</sup>	118.5	( 4.99 )
Center of Gravity from Rear Face of Flywheel Housing - in.(mm) .....	27.7	( 704 )
Center of Gravity Above Crankshaft Centerline - in.(mm) .....	5.5	( 140 )
Reference Installation Drawing		
--Fan to Flywheel Engine.....	4915105	
--Heat Exchanger Cooled Engine.....	4061315	

### ENGINE MOUNTING

Maximum Allowable Bending Moment at Rear Face of Block - lb.ft. (N·m)..	1000	( 1356 )
---	------	----------

### EXHAUST SYSTEM

Maximum Allowable Back Pressure - in.Hg (kPa).....	3.0	( 10 )
Standard Exhaust Pipe Diameter - in. (mm).....	5.0	( 127 )

### AIR INDUCTION SYSTEM

Maximum Allowable Intake Air Restriction		
--With Clean Filter Element - in. H <sub>2</sub> O (kPa).....	15	( 3.74 )
--With Dirty Filter Element - in. H <sub>2</sub> O (kPa) .....	25	( 6.22 )
Minimum Dirt Holding Capacity - g/CFM ( g/L/s ).....	25	( 53 )
Maximum Allowable Intake Air Temperature ΔT - °F (°C).....	30	( 17 )

### COOLING SYSTEM

Coolant Capacity - Engine Only - U.S. gal (L).....	5.5	( 20.8 )
- With Radiator - U.S. gal (L).....	16.0	( 60.6 )
- With Heat Exchanger - U.S. gal (L).....	13.0	( 49.2 )
Maximum Coolant Friction Head External to Engine - PSI (kPa).....	6	( 41 )
Maximum Static Head of Coolant (exclusive of Pressure Cap) - PSI (kPa) ..	15	( 103 )
Maximum Static Head of Coolant Above Engine Crank Centerline -ft. (m) ..	46	( 14.0 )
Standard Thermostat (Modulating) Range - °F (°C) .....	180 - 202	( 82 - 94 )
Minimum Allowable Pressure Cap -PSI (kPa).....	7.0	( 48.2 )
Maximum Coolant Temperature - °F (°C).....	205	( 96 )
Maximum Allowable Top Tank Temperature for Standby / Prime Power - °F	220 / 212	( 104 / 100 )

Minimum Recommended Top Tank Temperature - °F (°C).....	160	( 71 )
Minimum Coolant Expansion Space - % of System Capacity .....	5	
Minimum Coolant Makeup Capacity - U.S. gal (L).....	1.1	( 4.2 )
Engine Water Flow - GPM (L/s) .....	79	( 5 )

#### Fan to Flywheel Engine

Recommended Standard Fan Diameter - in. (mm).....	34	( 864 )
Fan to Crankshaft Ratio.....	1.2	
Fan Speed - r/min.....	1800	
Fan Power - HP (kW).....	19.0	( 14.2 )
Standard Fan Air Flow - CFM (m <sup>3</sup> /s).....	25003	( 11.8 )

#### Heat Exchanger Cooled Engine

Raw Water Flow - GPM (L/s) .....	51.5	( 3.25 )
Maximum Raw Water Pump Initial Suction Lift - ft. (m).....	9.4	( 2.8 )
Maximum Raw Water Pump Initial Discharge Lift - ft. (m).....	32.8	( 9.7 )
Raw Water Pump Power - HP (kW).....	2.7	( 2 )
Maximum Raw Water Pressure at Engine Outlet -PSI (kPa).....	15	( 103 )
Maximum Inlet Restriction at Raw Water Pump - in.Hg (kPa).....	10	( 34 )
Minimum Raw Water Pipe Size - in. (mm).....	2	( 51 )

### LUBRICATION SYSTEM

Oil Pressure @ Idle Speed - PSI (kPa).....	15 Min	( 103 ) Min
@ Governed Speed - PSI (kPa).....	35-50	( 241 - 345 )
Maximum Allowable Oil Temperature - °F (°C).....	250	( 121 )
Maximum Oil Consumption - U.S.qt./h (L/h).....	0.25	( 0.24 )
Oil Flow - GPM (L/s) .....	34.9	( 2.2 )
Oil Pan Capacity - Low / High - U.S. gal. (L).....	7.5 / 9.5	( 28.4 / 36.0 )
Total System Capacity - U.S. gal. (L).....	10.2	( 38.6 )
Angularity of Oil Pan - Front Down/Front Up/Side to Side.....	38°/38°/38°	

### FUEL SYSTEM

Type Injection System.....	Direct Injection Cummins PT	
<b>Maximum Allowable Restriction to Fuel Pump</b>		
-- With Clean Fuel Filter - in.Hg (kPa).....	4.0	( 13.5 )
-- With Dirty Fuel Filter - in.Hg (kPa).....	8.0	( 27.1 )
<b>Maximum Allowable Head on Injector Return Line</b>		
-- With Check Valve - in.Hg (kPa).....	6.5	( 22.0 )
-- Without Check Valve - in.Hg (kPa).....	2.5	( 8.5 )
Minimum Fuel Supply Line Size - in. (mm).....	0.625	( 16 )
Minimum Fuel Return Line Size - in. (mm).....	0.5	( 13 )
Maximum Fuel Pump Supply - U.S.gal/h (L).....	81	( 305 )
Fuel Rail Pressure - PSI (kPa).....	165	( 1141 )
Maximum Fuel Temperature °F (°C).....	160	( 71 )

### ELECTRICAL SYSTEM

Minimum Recommended Battery Capacity ( 24V )		
-- Cold Soak (No Load) - CCA.....	900	
- Minimum Reserved Capacity - CCA.....	320	
-- Cold Soak (With Load) - CCA.....	900	
- Minimum Reserved Capacity - CCA.....	320	
Maximum Allowable Resistance of Cranking Circuit - ohm.....	0.002	
Standard Cranking Motor (Heavy Duty , Positive Engagement) - volt.....	24	
Standard Battery Charging System , Negative Ground - ampere.....	35	

## PERFORMANCE DATA

Idle Speed - r/min .....	575 - 650
Maximum No-Load Governed Speed - r/min .....	1800
Maximum over Speed Capability - r/min .....	2700
Minimum Crankshaft Rotation for unaided Cold Start - r/min.....	150
Minimum Torque for unaided Cold Start - lb..ft. (N·m).....	375 ( 509 )
Exhaust Sound Pressure at 1m from Exhaust Outlet -1500r/min -dBA.....	N/A

All data is based on :

- Engine Operating with fuel system, water pump, lubricating oil pump, air cleaner and exhaust silencer, fan, and optional driven components.
- Engine operating with fuel corresponding to grade No.2-D per **ASTM D975**.
- ISO 3046**, Part1, Standard Reference Conditions of : Barometric Pressure:100kPa(29.5in.Hg); Altitude: 110m (361ft.); Air Temperature: 25°C (77° F) ; Relative Humidity: 30% .
- This Data Sheet includes both air-cooled (Fan/Radiator) & raw water cooled (Heatexchanger/Raw Water Pump) type engine.
- N.A. - Data is Not Available
- N/A - Not Applicable to this Engine
- TBD - To Be Determined

	Prime Power		Standby Power	
	50Hz		50Hz	
	1500		1500	
Governed Engine Speed - r/min.....	380	(284)	430	(321)
Gross Engine Power Output - HP (kW) .....	1333	(1808)	1507	(2044)
Torque lb..ft. (N·m).....	235	(1623)	266	(1834)
Brake Mean Effective Pressure - PSI (kPa) .....	1500	(7.62)	1500	(7.62)
Piston Speed - ft./min (m/s).....	30	(22)	30	(22)
Friction Horsepower - HP (kW).....	795	(375)	885	(418)
Intake Air Flow - CFM (L/s) .....	18.0	(68 )	20.4	(77 )
Fuel Consumption - U.S.gal/h (L/h).....	905	( 485 )	930	( 499 )
Exhaust Gas Temperature (After Turbine) - °F (°C).....	2067	(980)	2301	(1090)
Exhaust Gas Flow (After Turbine) - CFM (L/s).....	26.1 : 1		25.7 : 1	
Air to Fuel Ratio.....	1960	(34)	2220	(39)
Heat Radiation - BTU (kW).....	11740	(206)	13320	(234)
Heat Rejection to Coolant - BTU (kW).....	9780	(172)	11100	(195)

Engine Model: NTA855-G1B

Data Sheet: DS-819E

Date: 2007-1-25

**CHONGQING CUMMINS ENGINE CO. LTD.** CHONGQING, CHINA, 400031

All Data is Subject to Change Without Notice - contact CCEC for most recent data . Tel : 86-400-889-9